

IN THE CLAIMS

Please amend Claims 10 and 25-28, and add new Claims 29-37 as follows:

5
1. (Original) A method of transmitting data across a high-speed serial bus, the method comprising:

in accordance with a first TX symbol clock:

generating a 10-bit symbol on an IEEE 1394-compliant PHY having a port
10 interface;

placing the generated 10-bit symbol on the port interface;

scrambling the 10-bit symbol;

encoding the 10-bit symbol;

placing the 10-bit symbol in a FIFO;

15 in accordance with a second TX clock, the second TX clock running at a different speed than the first TX clock:

removing the 10-bit symbol from the FIFO;

deriving an 8-bit byte from the removed 10-bit symbol; and

sending the 8-bit byte to an IEEE 802.3-compliant PHY.

20 2. (Original) The method of claim 1, wherein a symbol is removed from the FIFO on four out of every five GMII TX clock cycles.

3. (Original) The method of claim 1, wherein a null 10-bit symbol is placed in the FIFO if there are no 10-bit symbols present in the FIFO.

4. (Original) The method of claim 1, wherein the 8-bit byte is derived from the 10-bit
25 symbol by using 8 bits from the extracted 10-bit symbol, and the two remaining bits are stored.

5. (Original) The method of claim 4, wherein a second 8-bit byte is derived by extracting from the FIFO a second 10-bit symbol and assembling an 8-bit byte from the stored two bits and six bits from the extracted second 10-bit symbol; the four remaining bits from the extracted second symbol are stored; and the second 8-bit byte is sent to the IEEE 802.3-compliant PHY.

30 6. (Original) The method of claim 5, wherein a third 8-bit byte is derived by extracting from the FIFO a third 10-bit symbol and assembling an 8-bit byte from the four stored bits and

four bits from the third extracted symbol; the six remaining bits from the extracted third symbol are stored; and the third 8-bit byte is sent to the IEEE 802.3-compliant PHY.

7. (Original) The method of claim 6, wherein a fourth 8-bit byte is derived by extracting from the FIFO a fourth 10-bit symbol, and assembling an 8-bit byte from the six stored bits and 2 bits from the extracted fourth 10-bit symbol; the eight remaining bits from the extracted fourth symbol are stored; and the fourth 8-bit byte is sent to the IEEE 802.3-compliant PHY.

8. (Original) The method of claim 7, wherein a fifth 8-bit byte is derived from the stored eight remaining bits and sent to the IEEE 802.3-compliant PHY.

9. (Original) The method of claim 1, further comprising, in accordance with a phase amplitude modulation clock, sending the received 8-bit byte from the IEEE 802.3-compliant PHY to a device in accordance with a phase amplitude modulation clock.

10. (Currently amended) A method of transmitting data across a high-speed serial bus, the method comprising:

receiving an 8-bit byte on an 802.3-compliant PHY;

in accordance with a GMII RX clock:

if the received 8-bit byte contains a null symbol, then deleting the null symbol;

else if the received 8-bit byte does not contain a null symbol, then storing the 8-bit byte in a first register;

receiving a second 8-bit byte that does not contain a null symbol and storing the second 8-bit byte in a second register;

assembling a 10-bit symbol from the 8-bit byte stored in the first register and appending two bits from the 8-bit byte stored in the second register; and

placing the assembled 10-bit symbol in a first FIFO;

in accordance with a second clock:

removing the 10-bit symbol from the first FIFO;

performing 8B10B and control decoding on the removed 10-bit symbol; and

placing the decoded 10-bit symbol in a second FIFO;

in accordance with a third clock:

removing the decoded 10-bit symbol from the second FIFO; and

sending the decoded 10-bit symbol to an IEEE 1394-compliant PHY.

11. (Original) The method of claim 10, wherein the second clock is phase locked to the third clock.

12. (Original) The method of claim 11, wherein frequency of null character deletion is used to control a phased locked loop, the phase locked loop associated with the second clock.

5 13. (Original) A method of transmitting data across a high-speed serial bus, the method comprising:

in accordance with a first TX symbol clock:

generating a 10-bit symbol on an IEEE 1394-compliant PHY having a port interface;

10 placing the generated 10-bit symbol on the port interface;

performing flagged encoding the 10-bit symbol;

placing the 10-bit symbol in a FIFO;

in accordance with a second TX clock, the second TX clock running at a different speed than the first TX clock:

15 removing the 10-bit symbol from the FIFO;

deriving an 8-bit byte from the removed 10-bit symbol; and

sending the 8-bit byte to an IEEE 802.3-compliant PHY.

14. (Original) The method of claim 13, wherein a symbol is removed from the FIFO on four out of every five GMII TX clock cycles.

20 15. (Original) The method of claim 13, wherein a null 10-bit symbol is placed in the FIFO

if there are no 10-bit symbols present in the FIFO.

16. (Original) The method of claim 13, wherein the 8-bit byte is derived from the 10-bit symbol by using 8 bits from the extracted 10-bit symbol, and the two remaining bits are stored.

25 17. (Original) The method of claim 16, wherein a second 8-bit byte is derived by extracting from the FIFO a second 10-bit symbol and assembling an 8-bit byte from the stored two bits and six bits from the extracted second 10-bit symbol; the four remaining bits from the extracted second symbol are stored; and the second 8-bit byte is sent to the IEEE 802.3-compliant PHY.

18. (Original) The method of claim 17, wherein a third 8-bit byte is derived by extracting from the FIFO a third 10-bit symbol and assembling an 8-bit byte from the four stored bits and four bits from the third extracted symbol; the six remaining bits from the extracted third symbol are stored; and the third 8-bit byte is sent to the IEEE 802.3-compliant PHY.

5 19. (Original) The method of claim 18, wherein a fourth 8-bit byte is derived by extracting from the FIFO a fourth 10-bit symbol, and assembling an 8-bit byte from the six stored bits and 2 bits from the extracted fourth 10-bit symbol; the eight remaining bits from the extracted fourth symbol are stored; and the fourth 8-bit byte is sent to the IEEE 802.3-compliant PHY.

10 20. (Original) The method of claim 19, wherein a fifth 8-bit byte is derived from the stored eight remaining bits and sent to the IEEE 802.3-compliant PHY.

21. (Original) The method of claim 13, further comprising, in accordance with a phase amplitude modulation clock, sending the received 8-bit byte from the IEEE 802.3-compliant PHY to a device in accordance with a phase amplitude modulation clock.

15 22. (Original) A method of transmitting data across a high-speed serial bus, the method comprising:

receiving an 8-bit byte on an IEEE 802.3-compliant PHY;

in accordance with a GMII RX clock:

if the received 8-bit byte contains a null symbol, then deleting the null symbol;

20 else if the received 8-bit byte does not contain a null symbol, then storing the 8-bit byte in a first register;

receiving a second 8-bit byte that does not contain a null symbol and storing the second 8-bit byte in a second register;

assembling a 10-bit symbol from the 8-bit byte stored in the first register and

25 appending two bits from the 8-bit byte stored in the second register;

performing flagged decoding on the assembled 10-bit symbol and placing the assembled 10-bit symbol in a FIFO;

in accordance with a second clock:

removing the 10-bit symbol from the first FIFO; and

30 sending the decoded 10-bit symbol to an IEEE 1394-compliant PHY.

23. (Original) The method of claim 22, wherein a received data valid state is asserted on the IEEE 802.3-compliant PHY.

24. (Original) The method of claim 22, wherein the FIFO compensates for ppm differences between the IEEE 802.3-compliant PHY and the IEEE 1394-compliant PHY.

5 25. (Currently amended) An apparatus for transmitting ~~data~~ a data stream across a high-speed serial bus, the apparatus comprising:

an IEEE 802.3-compliant PHY having a GMII interface;

an IEEE 1394-compliant PHY in communication with the IEEE 802.3-compliant PHY;

a symbol insertion mechanism adapted to insert at least one symbol into the data stream

10 to facilitate transfer of the data stream at a rate associated with the high-speed serial bus;

a first connection, the first connection for transmitting data between a device and the IEEE 802.3-compliant PHY; and

a second connection, the second connection for transmitting data between a device and the IEEE 1394-compliant PHY.

15 26. (Currently amended) An apparatus for transmitting ~~data~~ a data stream across a high-speed serial bus, the apparatus comprising:

an IEEE 802.3-compliant PHY having a GMII interface;

an IEEE 1394-compliant PHY in communication with the IEEE 802.3-compliant PHY via a switch; the switch determining whether ~~data transmission~~ the data stream is ~~[[be]]~~ routed to
20 the IEEE 802.3-compliant PHY or the IEEE 1394-compliant PHY;

a symbol insertion mechanism adapted to insert at least one symbol into the data stream
to facilitate transfer of the data stream at a rate associated with the high-speed serial bus;

a first connection, the first connection for transmitting data between a device and the IEEE 802.3-compliant PHY; and

25 a second connection, the second connection for transmitting data between a device and the IEEE 1394-compliant PHY.

27. (Currently amended) The apparatus of claim ~~[[25]]~~ 26, further comprising an autonegotiation mechanism, the autonegotiation mechanism determining whether data is to be routed between the IEEE 802.3-compliant PHY and the IEEE 1394-compliant PHY.

28. (Currently amended) The apparatus of claim [[26]] 27, wherein the autonegotiation mechanism determines whether data is to be routed through the IEEE 802.3-compliant PHY to the first connection.

29. (New) A method of transmitting data across a high-speed serial bus, the method comprising:

receiving an 8-bit byte on an 802.3-compliant PHY;

in accordance with a GMII RX clock:

if the received 8-bit byte contains a null symbol, then deleting the null symbol;

else if the received 8-bit byte does not contain a null symbol, then storing the 8-bit byte in a first register;

receiving a second 8-bit byte that does not contain a null symbol and storing the second 8-bit byte in a second register;

assembling a 10-bit symbol from the 8-bit byte stored in the first register and appending two bits from the 8-bit byte stored in the second register; and

placing the assembled 10-bit symbol in a first FIFO;

in accordance with a second clock:

removing the 10-bit symbol from the first FIFO;

performing 8B10B and control decoding on the removed 10-bit symbol; and

placing the decoded 10-bit symbol in a second FIFO;

in accordance with a third clock:

removing the decoded 10-bit symbol from the second FIFO; and

sending the decoded 10-bit symbol to an IEEE 1394-compliant PHY;

wherein the second clock is phase locked to the third clock, the frequency of null character deletion is used to control a phased locked loop, and the phase locked loop is associated with the second clock.

30. (New) A method of transmitting data across at least a high-speed serial bus, the method comprising:

receiving a first multi-bit byte on a first physical interface;

in accordance with a first clock:

storing the first multi-bit without any null symbol in a first storage location;

receiving a second multi-bit byte that does not contain a null symbol and storing the second multi-bit byte in a second storage location;

assembling a multi-bit symbol from the byte stored in the first location and at least a portion of the byte stored in the second location; and

5 placing the multi-bit symbol in a first buffer;

in accordance with a second clock, moving the multi-bit symbol from the first buffer to a second buffer, said act of moving further comprising at least decoding the multi-bit symbol to produce a decoded symbol; and

10 in accordance with a third clock, sending the decoded symbol to a second physical interface.

31. (New) The method of claim 30, wherein said second clock is phase locked to the third clock.

32. (New) The method of claim 31, wherein said second interface utilizing a different communication protocol than the first interface.

15 33. (New) A method of transmitting data across a high-speed serial bus, the method comprising:

in accordance with a first clock:

generating a first multi-bit symbol on first physical interface having a port;

placing the generated first symbol on the port;

20 scrambling the first symbol;

encoding the scrambled first symbol;

placing the scrambled symbol in a buffer;

in accordance with a second clock running at a different speed than the first clock:

deriving a multi-bit byte from the scrambled symbol; and

25 sending the multi-bit byte to a second physical interface, the second interface utilizing a different communication protocol than the first interface.

34. (New) The method of claim 33, further comprising removing the scrambled symbol from the buffer before performing said act of deriving.

30 35. (New) The method of claim 33, further comprising placing a null multi-bit symbol in the buffer if there are no scrambled multi-bit symbols present in the buffer.

Application No. : **10/749,325**
Filed : **December 29, 2003**

36. (New) The method of claim 33, wherein the multi-bit byte is derived from the first symbol by using 8 bits from the scrambled symbol.

37. (New) The method of claim 33, further comprising, in accordance with a phase amplitude modulation clock, sending the received multi-bit byte from the second interface to a
5 device in accordance with a phase amplitude modulation clock.